2.	IN THE SPECIFICATION

(a) TITLE OF THE INVENTION

System for processing broadcasted signals
System using a URL to retrieve information for controlling a tuning means

(b) CROSS-REFERENCE TO RELATED APPLICATIONS

The present application claims priority of European patent application 97203667.7, filed on November 24, 1997.

5
(c) STATEMENT REGARDING FEDRALLY SPONSORED RESEARCH OR
DEVELOPMENT

Not applicable

10

15

(d) INCORPORATION-BY-REFERENCE OF MATERIAL SUBMITTED ON A COMPACT DISC

Not applicable

(e) BACKGROUND OF THE INVENTION

(1) Field of the Invention

The present invention relates to a system for controlling a tuning means for receiving broadcasted signals according to the preamble of claim 1.

(2) Description of Related Art

Bit,

Such systems are known and are used in analogue TV sets and digital TV sets. Digital TV sets operate in accordance with the DVB (Digital Video Broadcasting) standard and recently introduced digital TV sets are enhanced with peripherals like modems for user-feedback. Further, microcomputers, in particular PC's, are generally known for which recently internal or external devices are introduced for receiving broadcasted signals, such as analogue or DVB signals. An example of such a device is an integrated network PC card. Pc's with modems are widely used to access the internet Internet, wherein generally a browser program is used. These recent developments show an integration of PC and TV technology. GB-A-2 307 381 discloses an example of such an integrated system. In this known system a data file is obtained from the internet Internet and this data file is directly used to control the tuning means.

(f) BRIEF SUMMARY OF THE INVENTION

15

20

10

The present invention aims to provides an improved system of this type.

According to the invention a system of the above-mentioned type is provided characterized in that a number of URL's for broadcast services are defined as URL's, wherein the system comprises a memory for storing tuning information for a number of broadcast services, and means for selecting a URL on a web page, the microcomputer being adapted to retrieve tuning information from the memory by means of a selected URL, wherein the microcomputer is

adapted to use the retrieved tuning information for controlling the tuning means to receive broadcast signals from the corresponding broadcast service.

In the system of the invention the information obtained by selecting a specific URL corresponding to a specific broadcast service is used by the system, i.e. the microcomputer to retrieve the corresponding tuning information from an internal memory. In this manner a flexible system is obtained, wherein the tuning information for the broadcast service can be adapted to the location where the system is used. Thereby the same web pages with URL's can be used world wide, while it is possible to use the information contained in the URL to provide the tuning means tuning information applicable to local broadcast services, which tuning information can be different for different locations.

(g) BRIEF DESCRIPTION OF THE VIEW OF THE DRAWING

10

15

20

25

The invention will be further explained by reference to the drawing in which the software architecture of an embodiment of the system according to the invention is schematically shown.

(h) DETAILED DESCRIPTION OF THE INVENTION

A system for processing Digital Video Broadcasting (DVB) signals comprises a microcomputer not further shown. The microcomputer is provided with a DVB device 1 also called a network card. This DVB device can be tuned to a specific transport stream as controlled by a driver 2 as will be further explained hereinafter. The microcomputer is connected to the internet_Internet and to a

MPEG signal source, for example through a satellite, cable or terrestrial transmission. When the DVB device 1 is tuned to a specific transport stream, the video, audio, or data information received is further processed in a manner known per se so that for example the video information will be displayed on the microcomputer monitor.

5

15

20

In the embodiment shown in the drawing, a browser program 3 indicated as a block-3, is used to access the internet Internet and by going to a certain web site a web page can be displayed on the monitor in a manner known per se. Such web pages may contain one or more URL's providing a connection to another web site by clicking on such a URL, as is well known.

According to the present invention URL's are used to tune the DVB device 1 to a specific DVB service in the following manner. Activating a selected URL results in providing an IP address by the browser program 3 to an IP stack 4. The IP stack 4 computes a so-called MAC (Medium Access Control) address from the IP address received from the browser program 3. A control program 5 which is part of the driver 2, receives this MAC address and looks up corresponding tuning information and a service identification from a navigation table 6 stored in a memory. This tuning information and a service identification are used by the driver 2 to control the DVB device 1 to tune to the DVB service corresponding to the selected URL. As the operation for tuning the network card or DVB device 1 to the correct transport stream is generally known in DVB technology, this tuning is not further described.

In this manner a standard browser program 3 with IP stack 4 which is also standard in multicast Ethernet applications, can be used to tune the network card to the DVB service. Thereby the system provides a full integration of PC and DVB TV technology in a simple manner. The network card/DVB device 1 can be tuned to a desired DVB service by simply clicking for example on the name of this DVB service.

It is noted that the retrieval of the tuning information from the navigation table is not restricted to the use of an IP address and computation of a MAC address. Other translations of the information in the URL into access information to retrieve the corresponding tuning information can be used.

10

15

20

According to a favourable embodiment the microcomputer is programmed such that the user can select a plurality of HTML pages for storing in memory so that frequently used web pages can be immediately displayed. For example an electronic program guide can be stored in this manner in memory in the microcomputer so that this program guide is immediately available to the user. In this program guide URL's can be embedded for each of the DVB services included in the program guide. By clicking on a URL for a selected DVB service the network cardDVB device 1 will be tuned to the desired DVB service. Of course it is also possible to have a default setting in the computer for storing certain HTML pages.

As an alternative for a system based on a PC as a microcomputer, the system can be based on a DVB TV set having a so-called set top box. This set top

box is preferably configured to cache a plurality of HTML pages as electronic program guide pages for the DVB TV set. As the set top box has a connection to the internet_Internet, one or more of the cached pages can provide URL's to internet_Internet sites instead of DVB services. In the present specification the word microcomputer is used to cover a PC, set top box or any other equivalent equipment. Further it is noted that the word <a href="internet_Interne

In an other embodiment of the system described, a special broadcast enhanced browser can be used, wherein the enhancement provides for processing of special URL syntax DVB addresses, wherein the normal <a href="mailto:internet_I

dvb://<original network id.>.<service id>/

10

In this example the DVB address is a 16 bit original network identifier in combination with a 16 bit service identifier. For compatibility with the internetInternet protocol, the two 16 bit values can be split into four 8 bit values. The DVB address will be indicated in this specification as <DVB address>.

In a further embodiment, the URL can contain an indication of the type of DVB service such as TV, radio and data, in the following manner:

dvb-tv://<DVB address>
dvb-radio://<DVB address>
DVB-data://<DVB address>.

Bit

It is noted that in the above described embodiments MPEG signals are mentioned as an example of broadcast signals. It is also possible to apply the invention in a system operating with other broadcast signals and also with analogue signals. It is further noted that the wording 'broadcast channel' covers any non IP based broadcast channel.